

ARCELORMITTAL Tubular Product ROMAN

TEVI CONSTRUCTII DIN-2448 / EN 10210-1 / S-355J2H / E-355

Diametru ext (mm)	Grosime perete (mm)																								
	4.5	5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
88.9	4.5	5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	15.5											
101.6	4.5	5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	15.5											
108.0	4.5	5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	15.5											
114.3	4.5	5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5										
127.0	4.5	5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5										
133.0	4.5	5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5										
139.7		5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5										
152.4		5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5										
159.0		5.0	5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5										
168.3			5.6	6.0	6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5	20.0									
177.8					6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5	20.0									
193.7					6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5	20.0									
219.1					6.3	7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5	20.0									
244.5						7.1	8.0	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5	20.0									
273.0							7.8	8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
299.0								8.8	10.0	11.0	12.0	12.5	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
323.9								8.4	10.0	11.0	12.0	12.5	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
355.6									9.5	11.0	12.0	12.5	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
368.0												12.7	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
377.0												12.7	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
406.4									9.5	11.0	12.0	12.5	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
419.0												12.7	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
457.0												12.7	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
473.0												12.7	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0
508.0												12.7	14.2	16.0	17.5	20.0	22.2	25.0	28.0	30.0	32.0	36.0	40.0	45.0	50.0